



Kingston Table Specifications:

Top Construction:

Kingston features heavy duty 14 gauge T or C-Legs with welded mounting plates and welded steel endcaps. Tables 60" and longer include steel support to prevent sagging. Special•T table tops are nominal 1-1/4" thick. Core is 1-1/8" thick 45# M3 industrial strength density particle board. The top surface is laminated with High Pressure Laminate (HPL) and the bottom is covered with a balance backer. Standard edges are T-mold and 3mm PVC. Other edges available*

- Fancy Vinyl
- Fancy Vinyl with Flat Sides
- Wood
- PurTech Urethane
- PurTech Urethane with Flat Sides
- PurWood Urethane
- PurWood Urethane with Flat Sides

*Custom edges may not be available with all shapes and sizes.
Web link: http://www.specialt.net/tables/training_room_tables/139



C-Leg with
caster option

Base Construction:

- Bolted/welded T or C leg
- Base height: 27.75"
- Columns: 2" diameter, 14 gauge steel
- Feet: 2" diameter, 14 gauge steel, steel endcaps
- Welded Mounting Plate: 5" x 8" x 7/32" steel
- Levelers: 1-3/8" diameter, 1/4-20 x 5/8" long, allow additional 1" upward height adjustment
- Finish: powder coat
- Load capacity: 330 lbs. (200kg) vertical load rating per base

Options:

- Casters
- Folding legs
- Adjustable height
- Counter height (36")
- Bar height (42")
- Grommet
- Wire management
- Modesty panel
- Power and data
- Table connector



Kingston Table with folded T-legs
and folding laminate modesty
panel

Additional Information:

- For easy installation, tops are pre-drilled. Refer to the table below for leg positioning.
- **Kingston** is available in 18" - 36" width and up to 96" long. Tables over 96" long require third leg.
- 36" wide tables have welded base and are not available with the following options: casters, folding, adjustable height, counter height or bar height.
- Not all options are available for each table size.
- Tables with casters that will be used in conjunction with other tables require table connector for proper leveling.
- Standard lead time is 15 business days. Large orders may require additional time.

36" - 48"	3.5" from the edge to column center
54"	4" from the edge to column center
60" - 72"	6" from the edge to column center
84"	12" from the edge to column center
96"	12" from the edge to column center



Compliant with
BIFMA X7.1 Standard